

ANTHEM ADVANCED SL 2

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Mariana Blue/Icicle White
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DEMPER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	SRAM TwistLoc Ultimate
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
ZADEL	Giant Grit
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Eagle 90 mechanical, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM Eagle 90 Transmission
REMMEN	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano SLX BL-M6200
CASSETTE	SRAM 70 1270, 10x52
AANDRIJVING	SRAM 70 Transmission
CRANKSET	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCA WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Sapim
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 5.499,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis lengte (mm)	400	420	465	495				
Zitbuis hoek	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Frame Lengte (horizontaal) (mm)	576 574	602 600	624 623	651 650				
Balhoofdbuis Lengte (mm)	90	95	105	115				
Balhoofdbuis Hoek	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Wielbasis (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Liggende achtervork lengte (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Stand Over Height (mm)	769 775	764 771	758 763	751 758				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	60	70	70	80				
Cranklengte (mm)	170	170	175	175				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.