

ANTHEM ADVANCED SL 2

GIANT



SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	Mariana Blue/Icicle White
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DEMPER	RockShox SidLux Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STYRSTEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SETEPINNE	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADEL	Giant Grit
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Eagle 90 mechanical, 1x12
FRONTGIR	N/A
BAKGIR	SRAM Eagle 90 Transmission
BREMSE	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
BREMSEHENDLER	Shimano SLX BL-M6200
KASSETT	SRAM 70 1270, 10x52
KJEDE	SRAM 70 Transmission
KRANK	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EIKE	Sapim
DEKK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Top Tube Length (mm)	576 574	602 600	624 623	651 650				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Chain Stay Length (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Stand Over Height (mm)	769 775	764 771	758 763	751 758				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	60	70	70	80				
Crank Length (mm)	170	170	175	175				

Alle spesifikasjonene kan endres uten varsel.