

ANTHEM ADVANCED SL 2

GIANT



ŠPECIFIKÁCIE

| RÁM | |
|-------------------|---|
| VELKOSTI | S, M, L, XL |
| FARBY | Mariana Blue/Icicle White |
| RÁM | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| VIDLICA | RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout |
| TLMÍČ | RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate |
| KOMPONENTY | |
| RIADIDLÁ | Giant Integrated XC, composite, 780mm, 9-degree upsweep |
| GRIPY | SRAM TwistLoc Ultimate |
| PREDSTAVEC | Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm |
| SEDLOVKA | Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel / |
| SEDADLO | Giant Grit |
| PEDÁLE | N/A |
| POHON | |
| RADENIE | SRAM Eagle 90 mechanical, 1x12 |
| PREŠMYKAČ | N/A |
| PREHADZOVAČKA | SRAM Eagle 90 Transmission |
| BRZDY | Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm |
| BRZDOVÉ PÁKY | Shimano SLX BL-M6200 |
| KAZETA | SRAM 70 1270, 10x52 |
| REŤAZ | SRAM 70 Transmission |
| KLUKY | SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm |
| STREDOVÉ ZLOŽENIE | SRAM DUB, press fit |

| KOLESÁ | |
|------------|--|
| RÁFIKY | Giant XCA WheelSystem |
| NÁBOJE | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt |
| ŠPICE | Sapim |
| PNEUMATIKY | Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless |
| DOPLNKY | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

Cena: 5 799 €

GEOMETRIA

| RÁM | S | M | L | XL |
|--|---------------|---------------|---------------|---------------|
| Dĺžka sedlovej trubky (mm) | LOW HIGH | LOW HIGH | LOW HIGH | LOW HIGH |
| Uhol sedlovej trubky | 75,5° 76,0° | 75,5° 76,0° | 75,5° 76,0° | 75,5° 76,0° |
| Dĺžka hornej rámovej trubky (mm) | 576 574 | 602 600 | 624 623 | 651 650 |
| Dĺžka hlavovej trubky (mm) | 90 | 95 | 105 | 115 |
| Uhol hlavovej trubky | 66,5° 67,0° | 66,5° 67,0° | 66,5° 67,0° | 66,5° 67,0° |
| Offset vidlice (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 116 112,2 | 115,9 112,2 | 115,9 112,2 | 115,8 112,2 |
| Rázvor (mm) | 1141 1140 | 1168 1167 | 1192 1191 | 1221 1220 |
| Dĺžka zadnej stavby (mm) | 437 435 | 437 435 | 437 435 | 437 435 |
| Rozdiel zadnej voči stredovej osi - BB DROP (mm) | 51 45 | 51 45 | 52 45 | 52 45 |
| Stack - výška riadenia (mm) | 602 599 | 607 603 | 616 612 | 626 622 |
| Reach (mm) | 420 425 | 445 450 | 465 470 | 490 495 |
| Výška rámu od zeme (mm) | 769 775 | 764 771 | 758 763 | 751 758 |
| Šírka riaditok (mm) | 780 | 780 | 780 | 780 |
| Dĺžka predstavca (mm) | 60 | 70 | 70 | 80 |
| Dĺžka kľúku (mm) | 170 | 170 | 175 | 175 |

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.