

ANTHEM ADVANCED SL 2

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
KRMILO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
OPORA KRMILA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
OPORA SEDEŽA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm XL: 140-170mm travel / 30.9 x 530mm
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90 mechanical, 1x12
ZADNJI MENJALNIK	SRAM Eagle 90 Transmission
ZAVORE	Shimano Deore BR-M6220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano Deore BL-M6200
VERIŽNIK	SRAM 70 1270, 10x52
VERIGA	SRAM 70 Transmission
GONILKE Z VERIŽNIKI	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCA WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODATKI	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		420		465		495	
Kot sedežne cevi	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Višina glave okvirja (mm)	90		95		105		115	
Krmični kot	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Medosna razdalja (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Dolžina cevi ob verigi (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Oddaljenost zgornje cevi od gonilne osi (mm)	602	599	607	603	616	612	626	622
Doseg (mm)	420	425	445	450	465	470	490	495
Višina zgornje cevi (mm)	769	775	764	771	758	763	751	758
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	60		70		70		80	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.