

ANTHEM ADVANCED SL 2

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Mariana Blue/Icicle White
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAKDÄMPARE	RockShox SidLux Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREPPAR	SRAM TwistLoc Ultimate
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADEL	Giant Grit
PEDALER	N/A
DRIVLINA	
VÄXLAR	SRAM Eagle 90 mechanical, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM Eagle 90 Transmission
BROMSAR	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano SLX BL-M6200
KASSETT	SRAM 70 1270, 10x52
KEDJA	SRAM 70 Transmission
VEVPARTI	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Sapim
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 63 990,00 kr

GEOMETRY

RAM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Längd sadelrör (mm)	400		420		465		495	
Vinkel sadelrör	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Topprörets längd (mm)	576	574	602	600	624	623	651	650
Styrhuvud Längd (mm)	90		95		105		115	
Vinkel styrhuvud	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Gaffelvinkel (mm)	44		44		44		44	
Spår (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Hjulbas (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Kedjestagslängd (mm)	437	435	437	435	437	435	437	435
Nedre fäste Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stå över höjden (mm)	769	775	764	771	758	763	751	758
Styrets bredd (mm)	780		780		780		780	
Stamlängd (mm)	60		70		70		80	
Vevlängd (mm)	170		170		175		175	

All specifications listed are subject to change without notice.