

ANTHEM ADVANCED SL 2

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Mariana Blue/Icicle White
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90 mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	Shimano SLX BR-M6220, hydraulic, Giant RT66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano SLX BL-M6200
CASSETTE	SRAM 70 1270, 10x52
CHAIN	SRAM 70 Transmission
CRANKSET	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCA WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°				
Top Tube Length (mm)	576 574	602 600	624 623	651 650				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2				
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Chain Stay Length (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Stand Over Height (mm)	769 775	764 771	758 763	751 758				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	60	70	70	80				
Crank Length (mm)	170	170	175	175				

All specifications listed are subject to change without notice.