

ANTHEM ADVANCED SL 2

GIANT



產品規格

車架	
尺寸	S, M, L
顏色	Mariana Blue/Icicle White 藍/白
車架	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
前叉	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
避震器	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate

COMPONENTS	
車把手	Giant Integrated XC, composite, 780mm, 9-degree upsweep
把手帶/套	SRAM TwistLoc Ultimate
豎桿	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm
座桿	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel /
坐墊	Giant Grit
踏板	N/A

DRIVETRAIN	
變速把手	SRAM Eagle 90 mechanical, 1x12
前變速器	N/A
後變速器	SRAM Eagle 90 Transmission
煞車系統	Shimano SLX BR-M7100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
煞車把手	Shimano SLX BL-M7100
飛輪	SRAM 70 1270, 10x52
鍊條	SRAM 70 Transmission
大齒盤	SRAM 90 Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant XCA WheelSystem
花鼓	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
輻條	Sapim
外胎	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
其他	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: NT\$158,000

車架幾何

車架	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
座(立)管長 (mm)	400		420		465	
座(立)管角度	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
上管長度 (mm)	576 574		602 600		624 623	
頭管長度 (mm)	90		95		105	
頭管角度	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
前叉 (mm)	44		44		44	
Trail (mm)	116 112.2		115.9 112.2		115.9 112.2	
前後輪距 (mm)	1141 1140		1168 1167		1192 1191	
後下叉長度 (mm)	437 435		437 435		437 435	
五通下降高度 (mm)	51 45		51 45		52 45	
頭碗至五通高度 (mm)	602 599		607 603		616 612	
頭碗至五通長度 (mm)	420 425		445 450		465 470	
上管至地面高度 (mm)	769 775		764 771		758 763	
把手寬 (mm)	780		780		780	
龍頭長度 (mm)	60		70		70	
曲柄長度 (mm)	170		170		175	

*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。