

ANTHEM ADVANCED SL 3

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Carbon/Moon Dust
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
BAGDÆMPER	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
KOMPONENTER	
STYR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREB / STYRBÅND	Giant XC Pro, silicone
FREMPIND	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
SADELPIND	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
SADEL	Giant Grit
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	Shimano Deore mechanical, 1x12
FORSKIFTER	N/A
BAGSKIFTER	Shimano Deore
BREMSEER	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BREMSEGREB	Shimano BL-MT501
KASSETTE	Shimano M6100, 10x51
KÆDE	KMC X-12
KRANKSÆT	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	Praxis, press fit

HJUL	
FÆLGE	Giant XCA 29 WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Sapim
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 35.999,00 kr.

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørslængde (mm)	400	420	465	495				
Sadelrørsvinkel	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Overrørslængde (mm)	576 574	602 600	624 623	651 650				
Kronrørslængde (mm)	90	95	105	115				
Kronrørsvinkel	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Forgaffel fremspring (rake) (mm)	44	44	44	44				
Sti (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Akselafstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Kædestagslængde (mm)	437 435	437 435	437 435	437 435				
Krankboks drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Skridthøjde (mm)	769 775	764 771	758 763	751 758				
Styrbredde (mm)	780	780	780	780				
Frempindslængde (mm)	60	70	70	80				
Pedalarmslængde (mm)	170	170	175	175				

Alle de anførte specifikationer kan ændres uden varsel.