



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Carbon/Moon Dust
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STEM	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore
BRAKES	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano BL-MT501
CASSETTE	Shimano M6100, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant XCA 29 WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: ₹ 4,999.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.