

ANTHEM ADVANCED SL 3

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Luminous Lagoon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	Fox 34 SL Performance, 120mm, GRIP damper, 3 position, 15x110mm Kabolt thru-axle, 44mm offset
SHOCK	Fox Float SL Performance, 3 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 9-degree upsweep
GRIPS	Fox Twin-stick remote
STEM	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	Giant Contact Switch Core dropper S: 100mm travel / 30.9 x 350mm M: 125mm travel / 30.9 x 400mm L: 125mm travel / 30.9 x 400mm XL: 125mm travel / 30.9 x 400mm
SADDLE	Giant Core
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, SL-M6200, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, M7200, Shadow
BRAKES	Tektro Orion HD-M6041 4 piston, hydraulic, , Tektro 2.3mm rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro Orion HD-M6041
CASSETTE	Shimano Deore, M6200, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet M24, 30T, Alloy Chainring, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis press fit

WHEELS	
RIMS	Giant XCA Hookless Tubeless ready Alloy, 29", 30mm inner width
HUBS	"[F] Giant XCR Alloy, 6-bolt, 28H [R] Giant XCR Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt, 28H"
SPOKES	Sapim Laser
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP CS chain guide
LIMITS	
MAX TYRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

Price: \$7,499.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.