

ANTHEM ADVANCED SL 3

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Carbon/Moon Dust
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
DEMPER	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
ONDERDELEN	
STUUR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
HANDVATTEN	Giant XC Pro, silicone
STUURPEN	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
ZADEL	Giant Grit
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano Deore mechanical, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano Deore
REMMEN	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano BL-MT501
CASSETTE	Shimano M6100, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WIELSET	
VELGEN	Giant XCA 29 WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Sapim
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 4.499,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400	420	465	495				
Zitbuis Hoek	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Frame Lengte (horizontaal) (mm)	576 574	602 600	624 623	651 650				
Balhoofdbuis Lengte (mm)	90	95	105	115				
Balhoofdbuis Hoek	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Wielbasis (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Liggende achtervork lengte (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Stack (mm)	602 599	607 603	616 612	626 622				
Reach (mm)	420 425	445 450	465 470	490 495				
Stand Over Height (mm)	769 775	764 771	758 763	751 758				
Stuurpen breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	60	70	70	80				
Cranklengte (mm)	170	170	175	175				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.