

ANTHEM ADVANCED SL 3



SPECS

TELAIO	
TAGLIE	S, M, L, XL
TELAIO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORCELLA	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
AMMORTIZZATORE	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
COMPONENTISTICA	
MANUBRIO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
MANOPOLE	Giant XC Pro, silicone
ATTACCO MANUBRIO	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
REGGISSELLA	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x 395mm XL: 120mm travel / 30.9 x 395mm
SELLA	Giant Grit
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore SH-M6200, mechanical, 1x12
DERAGLIATORE POSTERIORE	Shimano Deore RD-M7200
FRENI	Tektro Orion HD-M6041, hydraulic, Tektro rotors [F]180mm, [R]160mm
COMANDI FRENO	Tektro Orion HD-M6041
PACCO PIGNONI	Shimano M6200, 10x51
CATENA	KMC X-12
GUARNITURA	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
MOVIMENTO CENTRALE	Praxis, press fit

RUOTE	
CERCHI	Giant XCA 29 WheelSystem
MOZZI	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt
RAGGI	Sapim
COPERTONI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA	tubeless prepared, MRP 1x CS chain guide
LIMITI	
SEZIONE MASSIMA SUPPORTATA	2.4"
DIMENSIONE MASSIMA DELLA CORONA	34T

Prezzo: 4.499,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Lunghezza Tubo Sella (mm)	400	420	465	495
Angolo Tubo Sella	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Lunghezza Tubo Orizzontale (mm)	576 574	602 600	624 623	651 650
Lunghezza Tubo Sterzo (mm)	90	95	105	115
Angolo Sterzo	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Interasse (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Lunghezza Carro Posteriore (mm)	437 435	437 435	437 435	437 435
Drop Movimento Centrale (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Altezza stand over (mm)	769 775	764 771	758 763	751 758
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	60	70	70	80
Lunghezza Pedivella (mm)	170	170	175	175

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.