



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Carbon/Moon Dust
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
KOMPONENTE	
KRMILO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
OPORA KRMILA	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
OPORA SEDEŽA	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
SEDEŽ	Giant Grit
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore mechanical, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore
ZAVORE	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano BL-MT501
VERIŽNIK	Shimano M6100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI	
OBROČI	Giant XCA 29 WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400	420	465	495				
Kot sedežne cevi	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650				
Višina glave okvirja (mm)	90	95	105	115				
Krmlini kot	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Medosna razdalja (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Dolžina cevi ob verigi (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Oddaljenost zgornje cevi od gonilne osi (mm)	602 599	607 603	616 612	626 622				
Doseg (mm)	420 425	445 450	465 470	490 495				
Višina zgornje cevi (mm)	769 775	764 771	758 763	751 758				
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	60	70	70	80				
Dolžina gonilke (mm)	170	170	175	175				

Vse navedene specifikacije se lahko spremenijo brez obvestila.