

# ANTHEM ADVANCED SL 3

GIANT



## SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Carbon/Moon Dust
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
BAKDÄMPARE	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
KOMPONENTER	
STYRE	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREPPAR	Giant XC Pro, silicone
STAM	Giant Integrated XC Alloy S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
SADEL	Giant Grit
PEDALER	N/A
DRIVLINA	
VÄXLAR	Shimano Deore mechanical, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano Deore
BROMSAR	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BROMSSPAKAR	Shimano BL-MT501
KASSETT	Shimano M6100, 10x51
KEDJA	KMC X-12
VEVPARTI	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	Praxis, press fit

HJUL	
FÄLGAR	Giant XCA 29 WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Sapim
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 52 990,00 kr

## GEOMETRY

RAM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Längd sadelrör (mm)	400		420		465		495	
Vinkel sadelrör	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Topprörets längd (mm)	576	574	602	600	624	623	651	650
Styrhuvud Längd (mm)	90		95		105		115	
Vinkel styrhuvud	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Gaffelvinkel (mm)	44		44		44		44	
Spår (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Hjulbas (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Kedjestagslängd (mm)	437	435	437	435	437	435	437	435
Nedre fäste Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stå över höjden (mm)	769	775	764	771	758	763	751	758
Styrets bredd (mm)	780		780		780		780	
Stamlängd (mm)	60		70		70		80	
Vevlängd (mm)	170		170		175		175	

All specifications listed are subject to change without notice.