

# ANTHEM ADVANCED SL 3

GIANT



## 產品規格

車架	
尺寸	S, M, L
顏色	藍/黑
車架	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
前叉	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
避震器	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout

COMPONENTS	
車把手	Giant Integrated XC鋁合金一體把, alloy, 780mm, 9-degree upsweep
把手帶/套	Giant XC Pro, silicone
豎桿	Giant Integrated XC Alloy鋁合金一體把 S:60mm, M:70mm, L:70mm
座桿	Giant Core dropper, remote S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm L: 120mm travel / 30.9 x
坐墊	Giant Grit
踏板	N/A

DRIVETRAIN	
變速把手	Shimano Deore mechanical, 1x12
前變速器	N/A
後變速器	Shimano Deore
煞車系統	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
煞車把手	Shimano BL-MT501
飛輪	Shimano M6100, 10x51
鍊條	KMC X-12
大齒盤	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET (B B)	Praxis, press fit

輪組	
輪圈	Giant XCA 29 WheelSystem
花鼓	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
輻條	Sapim
外胎	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
其他	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: NT\$128,000

## 車架幾何

車架	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
座(立)管長 (mm)	400		420		465	
座(立)管角度	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°
上管長度 (mm)	576	574	602	600	624	623
頭管長度 (mm)	90		95		105	
頭管角度	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°
前叉 (mm)	44		44		44	
Trail (mm)	116	112.2	115.9	112.2	115.9	112.2
前後輪距 (mm)	1141	1140	1168	1167	1192	1191
後下叉長度 (mm)	437	435	437	435	437	435
五通下降高度 (mm)	51	45	51	45	52	45
頭碗至五通高度 (mm)	602	599	607	603	616	612
頭碗至五通長度 (mm)	420	425	445	450	465	470
上管至地面高度 (mm)	769	775	764	771	758	763
把手寬 (mm)	780		780		780	
龍頭長度 (mm)	60		70		70	
曲柄長度 (mm)	170		170		175	

\*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。