

ANTHEM ADVANCED SL FRAME

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Iris Drift
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

WHEELS	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRY

FRAME	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Top Tube Length (mm)	576 574		602 600		624 623		651 650	
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Wheelbase (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Chain Stay Length (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Stand Over Height (mm)	769 775		764 771		758 763		751 758	
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

All specifications listed are subject to change without notice.