ANTHEM ADVANCED SL FRAME



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Iris Drift
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
DEMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

WIELSET	
EXTRA'S	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 3.699,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Zitbuis Lengte (mm)	400	420	465	495
Zitbuis Hoek	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Frame Lengte (horizontaal) (mm)	576 | 574	602 | 600	624 | 623	651 | 650
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	116 | 112,2	115,9 | 112,2	115,9 | 112,2	115,8 | 112,2
Wielbasis (mm)	1141 | 1140	1168 | 1167	1192 | 1191	1221 | 1220
Liggende achtervork lengte (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	52 | 45	52 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	626 | 622
Reach (mm)	420 | 425	445 | 450	465 | 470	490 | 495
Stand Over Height (mm)	769 | 775	764 | 771	758 | 763	751 | 758
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	60	70	70	80
Cranklengte (mm)	170	170	175	175

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.