

ANTHEM ADVANCED SL FRAME

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Iris Drift
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
AMORTIZER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
KRMILO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
OPORA KRMILA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

OBROČNIKI	
DODATKI	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		420		465		495	
Kot sedežne cevi	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Top Tube Length (mm)	576 574		602 600		624 623		651 650	
Višina glave okvirja (mm)	90		95		105		115	
Krmilni kot	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Medosna razdalja (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Dolžina cevi ob verigi (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Oddaljenost zgornje cevi od gonilne osi (mm)	602 599		607 603		616 612		626 622	
Doseg (mm)	420 425		445 450		465 470		490 495	
Višina zgornje cevi (mm)	769 775		764 771		758 763		751 758	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	60		70		70		80	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.