ANTHEM ADVANCED SL FRAME



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Iris Drift
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
BAKDÄMPARE	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

HJUL	
EXTRAFUNKTIONER	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 43 000,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Topprörets längd (mm)	576 | 574	602 | 600	624 | 623	651 | 650
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	116 | 112,2	115,9 | 112,2	115,9 | 112,2	115,8 | 112,2
Hjulbas (mm)	1141 | 1140	1168 | 1167	1192 | 1191	1221 | 1220
Kedjestagslängd (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Nedre fäste Drop (mm)	51 | 45	51 | 45	52 | 45	52 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	626 | 622
Reach (mm)	420 | 425	445 | 450	465 | 470	490 | 495
Stå över höjden (mm)	769 | 775	764 | 771	758 | 763	751 | 758
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	60	70	70	80
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.