

# ANTHEM ADVANCED SL FRAMESET



## SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Electrical Storm
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	N/A
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	N/A
SADDLE	N/A
PEDALS	N/A

## WHEELS

EXTRAS 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRY

FRAME	S	M	L	XL
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°
Top Tube Length (mm)	576   574	602   600	624   623	651   650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116   112,2	115,9   112,2	115,9   112,2	115,8   112,2
Wheelbase (mm)	1141   1140	1168   1167	1192   1191	1221   1220
Chain Stay Length (mm)	437   435	437   435	437   435	437   435
Bottom Bracket Drop (mm)	51   45	51   45	52   45	52   45
Stack (mm)	602   599	607   603	616   612	626   622
Reach (mm)	420   425	445   450	465   470	490   495
Stand Over Height (mm)	769   775	764   771	758   763	751   758
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

All specifications listed are subject to change without notice.