

# ANTHEM ADVANCED SL FRAMESET

**GIANT**



## SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Electrical Storm
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	N/A
BAGDÆMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
FREMPIND	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELPIND	N/A
SADEL	N/A
PEDALER	N/A

## HJUL

EKSTRA 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 29.499,00 kr.

## GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørslængde (mm)	400		420		465		495	
Sadelrørsvinkel	75,5°   76,0°		75,5°   76,0°		75,5°   76,0°		75,5°   76,0°	
Overrørslængde (mm)	576   574		602   600		624   623		651   650	
Kronrørslængde (mm)	90		95		105		115	
Kronrørsvinkel	66,5°   67,0°		66,5°   67,0°		66,5°   67,0°		66,5°   67,0°	
Forgaffel fremspring (rake) (mm)	44		44		44		44	
Sti (mm)	116   112,2		115,9   112,2		115,9   112,2		115,8   112,2	
Akselafstand (mm)	1141   1140		1168   1167		1192   1191		1221   1220	
Kædestagslængde (mm)	437   435		437   435		437   435		437   435	
Krankboks drop (mm)	51   45		51   45		52   45		52   45	
Stack (mm)	602   599		607   603		616   612		626   622	
Reach (mm)	420   425		445   450		465   470		490   495	
Skridthøjde (mm)	769   775		764   771		758   763		751   758	
Styrbredde (mm)	780		780		780		780	
Frempindslængde (mm)	60		70		70		80	
Pedalarmslængde (mm)	170		170		175		175	

Alle de anførte specifikationer kan ændres uden varsel.