

ANTHEM ADVANCED SL FRAMESET



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Electrical Storm
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GABEL	N/A
DÄMPFER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTEN	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
VORBAU	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATTELSTÜTZE	N/A
SATTEL	N/A
PEDALE	N/A

LAUFRÄDER	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Oberrohrlänge (mm)	576 574	602 600	624 623	651 650
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Radstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Überstandshöhe (mm)	769 775	764 771	758 763	751 758
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	70	70	80
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.