

ANTHEM ADVANCED SL FRAMESET

GIANT



SPECS

| FRAME | |
|------------|---|
| SIZES | S, M, L, XL |
| COLOURS | Electrical Storm |
| FRAME | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| FORK | N/A |
| SHOCK | RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate |
| COMPONENTS | |
| HANDLEBAR | Giant Integrated XC, composite, 780mm, 9-degree upsweep |
| STEM | Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm |
| SEATPOST | N/A |
| SADDLE | N/A |
| PEDALS | N/A |

WHEELS

EXTRAS 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: **£3,999.00**

GEOMETRY

| FRAME | S | M | L | XL |
|--------------------------|---------------|---------------|---------------|---------------|
| | LOW HIGH | LOW HIGH | LOW HIGH | LOW HIGH |
| Seat Tube Length (mm) | 400 | 420 | 465 | 495 |
| Seat Tube Angle | 75.5° 76.0° | 75.5° 76.0° | 75.5° 76.0° | 75.5° 76.0° |
| Top Tube Length (mm) | 576 574 | 602 600 | 624 623 | 651 650 |
| Head Tube Length (mm) | 90 | 95 | 105 | 115 |
| Head Tube Angle | 66.5° 67.0° | 66.5° 67.0° | 66.5° 67.0° | 66.5° 67.0° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 116 112.2 | 115.9 112.2 | 115.9 112.2 | 115.8 112.2 |
| Wheelbase (mm) | 1141 1140 | 1168 1167 | 1192 1191 | 1221 1220 |
| Chain Stay Length (mm) | 437 435 | 437 435 | 437 435 | 437 435 |
| Bottom Bracket Drop (mm) | 51 45 | 51 45 | 52 45 | 52 45 |
| Stack (mm) | 602 599 | 607 603 | 616 612 | 626 622 |
| Reach (mm) | 420 425 | 445 450 | 465 470 | 490 495 |
| Stand Over Height (mm) | 769 775 | 764 771 | 758 763 | 751 758 |
| Handlebar Width (mm) | 780 | 780 | 780 | 780 |
| Stem Length (mm) | 60 | 70 | 70 | 80 |
| Crank Length (mm) | 170 | 170 | 175 | 175 |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.