

ANTHEM ADVANCED SL FRAMESET



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Electrical Storm
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	N/A
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	N/A
SADDLE	N/A
PEDALS	N/A

WHEELS

EXTRAS 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Recommended Retail Price: **\$4,500.00**

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (inch)	15.7	16.5	16.5	18.3	18.3	19.5		
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°		
Top Tube Length (inch)	22.7 22.6	23.7 23.6	24.6 24.5	25.6 25.6				
Head Tube Length (inch)	3.5	3.7	4.1	4.5				
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°				
Fork Rake (inch)	1.7	1.7	1.7	1.7				
Trail (inch)	4.6 4.4	4.5 4.4	4.5 4.4	4.5 4.4				
Wheelbase (inch)	44.9 44.9	46 45.9	46.9 46.9	48.1 48				
Chain Stay Length (inch)	17.2 17.1	17.2 17.1	17.2 17.1	17.2 17.1				
Bottom Bracket Drop (inch)	2 1.8	2 1.8	2 1.8	2 1.8				
Stack (inch)	23.7 23.6	23.9 23.7	24.3 24.1	24.6 24.5				
Reach (inch)	16.5 16.7	17.5 17.7	18.3 18.5	19.3 19.5				
Stand Over Height (inch)	30.3 30.5	30.1 30.4	29.8 30	29.6 29.8				
Handlebar Width (inch)	30.7	30.7	30.7	30.7				
Stem Length (inch)	2.4	2.8	2.8	3.1				
Crank Length (inch)	6.7	6.7	6.9	6.9				

*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.