

ANTHEM ADVANCED SL FRAMESET

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Electrical Storm
RUNKO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HAARUKKA	N/A
ISKUNVAIMENNIN	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTIT	
OHJAUSTANKO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
OHJAINKANNATIN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATULATOLPPA	N/A
SATULA	N/A
POLKIMET	N/A

RENKAAT

LISÄTIEDOT 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suositusuhinta: 3 899,00 €

GEOMETRIA

RUNKO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	400	420	465	495				
Satulaputken kulma	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Vaakaputken pituus (mm)	576 574	602 600	624 623	651 650				
Emäputken pituus (mm)	90	95	105	115				
Emäputken kulma	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Haarukan offset (mm)	44	44	44	44				
Trail-mitta (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Akseliväli (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Takahaarukan alaputken pituus (mm)	437 435	437 435	437 435	437 435				
Keskiön pudotus (mm)	51 45	51 45	52 45	52 45				
Stack-mitta (mm)	602 599	607 603	616 612	626 622				
Reach-mitta (mm)	420 425	445 450	465 470	490 495				
Standover-mitta (mm)	769 775	764 771	758 763	751 758				
Ohjaustangon leveys (mm)	780	780	780	780				
Ohjainkannattimen pituus (mm)	60	70	70	80				
Kammen pituus (mm)	170	170	175	175				

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.