

ANTHEM ADVANCED SL FRAMESET

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Electrical Storm
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	N/A
DEMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADEL	N/A
ZADEL	N/A
PEDALEN	N/A

WIELSET	
EXTRA'S	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 3.699,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400		420		465		495	
Zitbuis Hoek	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Frame Lengte (horizontaal) (mm)	576 574		602 600		624 623		651 650	
Balhoofdbuis Lengte (mm)	90		95		105		115	
Balhoofdbuis Hoek	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Wielbasis (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Liggende achtervork lengte (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Stand Over Height (mm)	769 775		764 771		758 763		751 758	
Stuur breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	60		70		70		80	
Cranklengte (mm)	170		170		175		175	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.