



## SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Electrical Storm
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICA	N/A
AMORTIZER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
VOLAN	Giant Integrated XC, composite, 780mm, 9-degree upsweep
LULA VOLANA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
CIJEV SJEDALA	N/A
SJEDALO	N/A
PEDALE	N/A

## KOTAČI

**DODACI** 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRIJA

OKVIR	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dužina cijevi sjedala (mm)	400	420	465	485	515	535
Kut cijevi sjedala	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Dužina gornje cijevi (mm)	576	574	602	600	624	623
Dužina prednje cijevi (mm)	90	95	105	110	115	120
Kut vilice	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zakrivljenost vilice (offset) (mm)	44	44	44	44	44	44
Staza (mm)	116	112,2	115,9	112,2	115,9	112,2
Međuosovinski razmak kotača (mm)	1141	1140	1168	1167	1192	1191
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	437	435	437	435	437	435
Položaj osovine pogona (mm)	51	45	51	45	52	45
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	602	599	607	603	616	612
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	420	425	445	450	465	470
Prekoračna visina (mm)	769	775	764	771	758	763
Širina volana (mm)	780	780	780	780	780	780
Dužina lule volana (mm)	60	70	70	70	70	70
Dužina poluge pedale (mm)	170	170	170	170	175	175

Sve navedene specifikacije podložne su promjeni bez prethodne najave.