

# ANTHEM ADVANCED SL FRAMESET

**GIANT**



## SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Electrical Storm
TELAIO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORCELLA	N/A
AMMORTIZZATORE	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTISTICA	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
ATTACCO MANUBRIO	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
REGGISELLA	N/A
SELLA	N/A
PEDALI	N/A

## RUOTE

EXTRA 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Prezzo: 3.699,00 €

## GEOMETRIA

TELAIO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Lunghezza Tubo Sella (mm)	400	420	465	495				
Angolo Tubo Sella	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°				
Lunghezza Tubo Orizzontale (mm)	576   574	602   600	624   623	651   650				
Lunghezza Tubo Sterzo (mm)	90	95	105	115				
Angolo Sterzo	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°				
Rake Forcella (mm)	44	44	44	44				
Avancorsa (mm)	116   112,2	115,9   112,2	115,9   112,2	115,8   112,2				
Interasse (mm)	1141   1140	1168   1167	1192   1191	1221   1220				
Lunghezza Carro Posteriore (mm)	437   435	437   435	437   435	437   435				
Drop Movimento Centrale (mm)	51   45	51   45	52   45	52   45				
Stack (mm)	602   599	607   603	616   612	626   622				
Reach (mm)	420   425	445   450	465   470	490   495				
Altezza stand over (mm)	769   775	764   771	758   763	751   758				
Larghezza Manubrio c/c (mm)	780	780	780	780				
Lunghezza Attacco Manubrio (mm)	60	70	70	80				
Lunghezza Pedivella (mm)	170	170	175	175				

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.