

ANTHEM ADVANCED SL FRAMESET

GIANT



SPECS

FRAME	
SIZES	S, M, L
COLORS	エレクトロカルストーム
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle ※リアエンド型番 : SRAM UDH
FORK	N/A
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC Integrated, composite, 780mm, 9-degree Backsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Contact SLR XC Integrated, composite, -8-degree, S:60mm, M:70mm, L:70mm
SEATPOST	N/A
SADDLE	N/A
PEDALS	N/A

WHEELS

EXTRAS コンピューターマウント、SRAM Twistloc Ultimate、MRP chain guide

LIMITS

MAX TIRE CLEARANCE 2.4"

MAX CHAINRING SIZE 34T

Price: ¥638,000

GEOMETRY

FRAME	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623
Head Tube Length (mm)	90	95	105
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191
Chain Stay Length (mm)	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45
Stack (mm)	602 599	607 603	616 612
Reach (mm)	420 425	445 450	465 470
Stand Over Height (mm)	769 775	764 771	758 763
Handlebar Width (mm)	780	780	780
Stem Length (mm)	60	70	70
Crank Length (mm)	170	170	175

製品仕様は改良、部品供給上の都合により予告なしに変更する場合があります。あらかじめご了承ください。製品重量は個体差により実際と若干異なる場合がございます。また、Giant Premium Model (カーボンバイクおよびダブルサスペンションMTB)は、GPD(Giant Premium Dealer)のみで販売しております。対象販売店は、[店舗検索](#)にてご確認ください。