

# ANTHEM ADVANCED SL FRAMESET

**GIANT**



## SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Electrical Storm
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	N/A
DEMPER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	N/A
ZADEL	N/A
PEDALEN	N/A

## WIELSET

EXTRA'S 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 3.699,00

## GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400	420	465	495				
Zitbuis Hoek	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°				
Frame Lengte (horizontaal) (mm)	576   574	602   600	624   623	651   650				
Balhoofdbuis Lengte (mm)	90	95	105	115				
Balhoofdbuis Hoek	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°				
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	116   112,2	115,9   112,2	115,9   112,2	115,8   112,2				
Wielbasis (mm)	1141   1140	1168   1167	1192   1191	1221   1220				
Liggende achtervork lengte (mm)	437   435	437   435	437   435	437   435				
Bottom Bracket Drop (mm)	51   45	51   45	52   45	52   45				
Stack (mm)	602   599	607   603	616   612	626   622				
Reach (mm)	420   425	445   450	465   470	490   495				
Stand Over Height (mm)	769   775	764   771	758   763	751   758				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	60	70	70	80				
Cranklengte (mm)	170	170	175	175				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.