



SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Electrical Storm
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FURCA	N/A
SOC	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTE	
GHIDON	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PIPA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
TIJA SA	N/A
SA	N/A
PEDALE	N/A

ROTI

EXTRAS 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIE

CADRU	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Wheelbase (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stand Over Height (mm)	769	775	764	771	758	763	751	758
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

Toate specificatiile enumerate se pot schimba fara notificare prealabila.