

# ANTHEM ADVANCED SL FRAMESET

**GIANT**



## ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Electrical Storm
RÁM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VIDLICA	N/A
TLMÍČ	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTY	
RIADIDLÁ	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PREDSTAVEC	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEDOVKA	N/A
SEDADLO	N/A
PEDÁLE	N/A

KOLESÁ	
DOPLNKY	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Cena: 3 699 €

## GEOMETRIA

RÁM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dĺžka sedlovej trubky (mm)	400	420	465	495				
Uhol sedlovej trubky	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Dĺžka hornej rámovej trubky (mm)	576	574	602	600	624	623	651	650
Dĺžka hlavovej trubky (mm)	90	95	105	115				
Uhol hlavovej trubky	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Offset vidlice (mm)	44	44	44	44				
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Rázvor (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Dĺžka zadnej stavby (mm)	437	435	437	435	437	435	437	435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	51	45	51	45	52	45	52	45
Stack - výška riadenia (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Výška rámu od zeme (mm)	769	775	764	771	758	763	751	758
Šírka riaditok (mm)	780	780	780	780				
Dĺžka predstavca (mm)	60	70	70	80				
Dĺžka klúk (mm)	170	170	175	175				

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.