



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Electrical Storm
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	N/A
AMORTIZER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
KRMILO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
OPORA KRMILA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
OPORA SEDEŽA	N/A
SEDEŽ	N/A
PEDALA	N/A

OBROČNIKI

DODATKI 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400	420	465	495				
Kot sedežne cevi	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°				
Top Tube Length (mm)	576 574	602 600	624 623	651 650				
Višina glave okvirja (mm)	90	95	105	115				
Krmični kot	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°				
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Medosna razdalja (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Dolžina cevi ob verigi (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45				
Oddaljenost zgornje cevi od gonilne osi (mm)	602 599	607 603	616 612	626 622				
Doseg (mm)	420 425	445 450	465 470	490 495				
Višina zgornje cevi (mm)	769 775	764 771	758 763	751 758				
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	60	70	70	80				
Dolžina gonilke (mm)	170	170	175	175				

Vse navedene specifikacije se lahko spremenijo brez obvestila.