

ANTHEM ADVANCED SL FRAMESET

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Electrical Storm
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	N/A
BAKDÄMPARE	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	N/A
SADEL	N/A
PEDALER	N/A

HJUL	
EXTRAFUNKTIONER	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 43 499,00 kr

GEOMETRY

RAM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Längd sadelrör (mm)	400		420		465		495	
Vinkel sadelrör	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Topprörets längd (mm)	576 574		602 600		624 623		651 650	
Styrhuvud Längd (mm)	90		95		105		115	
Vinkel styrhuvud	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Gaffelvinkel (mm)	44		44		44		44	
Spår (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Hjulbas (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Kedjestagslängd (mm)	437 435		437 435		437 435		437 435	
Nedre fäste Drop (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Stå över höjden (mm)	769 775		764 771		758 763		751 758	
Styrets bredd (mm)	780		780		780		780	
Stamlängd (mm)	60		70		70		80	
Vevlängd (mm)	170		170		175		175	

All specifications listed are subject to change without notice.