

ANTHEM ADVANCED SL FRAMESET

GIANT



SPECS

| FRAME      |                                                                                                                     |
|------------|---------------------------------------------------------------------------------------------------------------------|
| SIZES      | S, M, L, XL                                                                                                         |
| COLORS     | Electrical Storm                                                                                                    |
| FRAME      | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| FORK       | N/A                                                                                                                 |
| SHOCK      | RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate                                           |
| COMPONENTS |                                                                                                                     |
| HANDLEBAR  | Giant Integrated XC, composite, 780mm, 9-degree upsweep                                                             |
| STEM       | Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm                                                          |
| SEATPOST   | N/A                                                                                                                 |
| SADDLE     | N/A                                                                                                                 |
| PEDALS     | N/A                                                                                                                 |

| WHEELS |                                                                   |
|--------|-------------------------------------------------------------------|
| EXTRAS | 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

GEOMETRY

| FRAME                    | S             |  | M             |  | L             |  | XL            |  |
|--------------------------|---------------|--|---------------|--|---------------|--|---------------|--|
|                          | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  |
| Seat Tube Length (mm)    | 400           |  | 420           |  | 465           |  | 495           |  |
| Seat Tube Angle          | 75.5°   76.0° |  | 75.5°   76.0° |  | 75.5°   76.0° |  | 75.5°   76.0° |  |
| Top Tube Length (mm)     | 576   574     |  | 602   600     |  | 624   623     |  | 651   650     |  |
| Head Tube Length (mm)    | 90            |  | 95            |  | 105           |  | 115           |  |
| Head Tube Angle          | 66.5°   67.0° |  | 66.5°   67.0° |  | 66.5°   67.0° |  | 66.5°   67.0° |  |
| Fork Rake (mm)           | 44            |  | 44            |  | 44            |  | 44            |  |
| Trail (mm)               | 116   112.2   |  | 115.9   112.2 |  | 115.9   112.2 |  | 115.8   112.2 |  |
| Wheelbase (mm)           | 1141   1140   |  | 1168   1167   |  | 1192   1191   |  | 1221   1220   |  |
| Chain Stay Length (mm)   | 437   435     |  | 437   435     |  | 437   435     |  | 437   435     |  |
| Bottom Bracket Drop (mm) | 51   45       |  | 51   45       |  | 52   45       |  | 52   45       |  |
| Stack (mm)               | 602   599     |  | 607   603     |  | 616   612     |  | 626   622     |  |
| Reach (mm)               | 420   425     |  | 445   450     |  | 465   470     |  | 490   495     |  |
| Stand Over Height (mm)   | 769   775     |  | 764   771     |  | 758   763     |  | 751   758     |  |
| Handlebar Width (mm)     | 780           |  | 780           |  | 780           |  | 780           |  |
| Stem Length (mm)         | 60            |  | 70            |  | 70            |  | 80            |  |
| Crank Length (mm)        | 170           |  | 170           |  | 175           |  | 175           |  |

All specifications listed are subject to change without notice.