

ANTHEM ADVANCED SL SE



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Stormfire Sprint
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
BAGDÆMPER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTER	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREB / STYRBÅND	Giant XC Pro, silicone
FREMPIND	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELIND	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SADEL	Giant Grit SLR
GEARGRUPPE	
SKIFTEGREB	SRAM AXS Pod, 1x12
BAGSKIFTER	SRAM XX SL Eagle Transmission
BREMSE	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BREMSEGREB	SRAM Motive ULT, custom color
KASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
KÆDE	SRAM XX SL Eagle Transmission
KRANKSÆT	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	CADEX Max XC WheelSystem, 30mm inner width
NAV	[F] CADEX Max XC, CenterLock [R]CADEX Max XC, 132t ratchet driver, CenterLock
EGER	CADEX Max XC carbon
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, MRP 1x CS chain guide
GRÆNSER	
MAX DÆKSTØRRELSE	2.4"
MAX KLINGE STØRRELSE	34T

Pris: 111.169,00 kr.

GEOMETRI

RAMME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sadelrørslængde (mm)	400	420	465	495
Sadelrørsvinkel	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Overrørslængde (mm)	576 574	602 600	624 623	651 650
Kronrørslængde (mm)	90	95	105	115
Kronrørsvinkel	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Akselafstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kædestagslængde (mm)	437 435	437 435	437 435	437 435
Krankboks drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Skridthøjde (mm)	769 775	764 771	758 763	751 758
Styrbredde (mm)	780	780	780	780
Frempindslængde (mm)	60	70	70	80
Pedalarmslængde (mm)	170	170	175	175

Alle de anførte specifikationer kan ændres uden varsel.