

ANTHEM ADVANCED SL SE

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Stormfire Sprint
FRAME	Advanced SL-grade composite front and rear triangles, UDH, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox SID Flight Attendant XC, 120mm, Race Day damper, Boost 15x110 thru-axle, 44mm offset
SHOCK	RockShox SIDLuxe Flight Attendant, RL3 damper, Solo Air
COMPONENTS	
HANDLEBAR	Giant Contact SLR Integrated XC, carbon, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STEM	Giant Contact SLR Integrated XC S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	RockShox Reverb AXS S: 125mm travel / 30.9 x 399mm M: 125mm travel / 30.9 x 399mm L: 150mm travel / 30.9 x 450mm XL: 150mm travel / 30.9 x 450mm
SADDLE	Giant Grit SLR
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, Rocker Paddle, 1x12
FRONT DERAILLEUR	NA
REAR DERAILLEUR	SRAM XX SL Eagle Transmission AXS
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT
CASSETTE	SRAM XS-1299, Eagle Transmission 10-52T
CHAIN	SRAM XX SL Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quarq power meter, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	CADEX Max XC, Hookless Tubeless ready Carbon, 29", 30mm inner width
HUBS	[F] CADEX M1-C hub, CenterLock, Ceramic bearings, 20H [R] CADEX M1-C120 Hub, 120T Helical-Bevel Ratchet Driver, CenterLock, Ceramic bearings, 24H
SPOKES	CADEX Super Aero Carbon Spoke
TYRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, MRP 1x SL TR2 chain guide
LIMITS	
MAX TYRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

Price: \$18,999.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.