

ANTHEM ADVANCED SL SE

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Stormfire Sprint
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SHOCK	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SADDLE	Giant Grit SLR
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT, custom color
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAIN	SRAM XX SL Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	CADEX Max XC WheelSystem, 30mm inner width
HUBS	[F] CADEX Max XC, CenterLock [R] CADEX Max XC, 132t ratchet driver, CenterLock
SPOKES	CADEX Max XC carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

Suggested Retail Price (CDN): \$16,499.00

FRAME GEOMETRY

FRAME	M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	420		465		495	
Seat Tube Angle	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
Top Tube Length (mm)	602 600		624 623		651 650	
Head Tube Length (mm)	95		105		115	
Head Tube Angle	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
Fork Rake (mm)	44		44		44	
Trail (mm)	115.9 112.2		115.9 112.2		115.8 112.2	
Wheelbase (mm)	1168 1167		1192 1191		1221 1220	
Chain Stay Length (mm)	437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		52 45		52 45	
Stack (mm)	607 603		616 612		626 622	
Reach (mm)	445 450		465 470		490 495	
Stand Over Height (mm)	764 771		758 763		751 758	
Handlebar Width (mm)	780		780		780	
Stem Length (mm)	70		70		80	
Crank Length (mm)	170		175		175	

All prices and specifications are subject to change without notice.