

ANTHEM ADVANCED SL SE



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Stormfire Sprint
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SHOCK	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SADDLE	Giant Grit SLR
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT, custom color
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAIN	SRAM XX SL Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	CADEX Max XC WheelSystem, 30mm inner width
HUBS	[F] CADEX Max XC, CenterLock [R]CADEX Max XC, 132t ratchet driver, CenterLock
SPOKES	CADEX Max XC carbon
TYRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

Price: €14,399.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

All specifications listed are subject to change without notice.