

ANTHEM ADVANCED SL SE



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	White/Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SHOCK	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEATPOST	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SADDLE	Giant Grit SLR
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAIN	SRAM XX SL Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Recommended Retail Price: \$14,500.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (inch)	15.7	16.5	18.3	19.5				
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (inch)	22.7 22.6	23.7 23.6	24.6 24.5	25.6 25.6				
Head Tube Length (inch)	3.5	3.7	4.1	4.5				
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (inch)	1.7	1.7	1.7	1.7				
Trail (inch)	4.6 4.4	4.5 4.4	4.5 4.4	4.5 4.4	4.5 4.4	4.5 4.4	4.5 4.4	4.5 4.4
Wheelbase (inch)	44.9 44.9	46 45.9	46.9 46.9	48.1 48				
Chain Stay Length (inch)	17.2 17.1	17.2 17.1	17.2 17.1	17.2 17.1				
Bottom Bracket Drop (inch)	2 1.8	2 1.8	2 1.8	2 1.8				
Stack (inch)	23.7 23.6	23.9 23.7	24.3 24.1	24.6 24.5				
Reach (inch)	16.5 16.7	17.5 17.7	18.3 18.5	19.3 19.5				
Stand Over Height (inch)	30.3 30.5	30.1 30.4	29.8 30	29.6 29.8				
Handlebar Width (inch)	30.7	30.7	30.7	30.7				
Stem Length (inch)	2.4	2.8	2.8	3.1				
Crank Length (inch)	6.7	6.7	6.9	6.9				

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*