

ANTHEM ADVANCED SL SE

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	White/Carbon
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
TIJERA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTIGUADOR	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTES	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
POTENCIA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
POSTE DE ASIENTO	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
ASIENTO	Giant Grit SLR
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM XX SL Eagle Transmission
FRENOS	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	SRAM Motive ULT
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CADENA	SRAM XX SL Eagle Transmission
MULTIPLICACIÓN	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant XCR WheelSystem
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAYOS	Carbon
NEUMÁTICOS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Precio: \$309,990.00

GEOMETRÍA

CUADRO	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Longitud de la Base del Poste de Asiento (mm)	400	420	465
Ángulo de la Base del Poste de Asiento	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Longitud del Tubo Superior (mm)	576 574	602 600	624 623
Longitud del Telescopio (mm)	90	95	105
Ángulo del Telescopio	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Rake (mm)	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2
Distancia entre Ejes (mm)	1141 1140	1168 1167	1192 1191
Longitud de Vaina Inferior (mm)	437 435	437 435	437 435
Caída del Eje de Centro (mm)	51 45	51 45	52 45
Stack (mm)	602 599	607 603	616 612
Reach (mm)	420 425	445 450	465 470
Altura del Tubo Superior al Suelo (mm)	769 775	764 771	758 763
Ancho del Manubrio (mm)	780	780	780
Longitud de la Potencia (mm)	60	70	70
Longitud de la Biela (mm)	170	170	175

Todas las especificaciones están sujetas a cambios sin previo aviso.