

ANTHEM ADVANCED SL SE



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Stormfire Sprint
RUNKO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HAARUKKA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
ISKUNVAIMENNIN	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMONENTIT	
OHJAUSTANKO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPIT	Giant XC Pro, silicone
OHJAINKANNATIN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATULATOLPPA	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SATULA	Giant Grit SLR
VOIMANSIIRTO	
VAIHDEVIPU	SRAM AXS Pod, 1x12
TAKAVAIHTAJA	SRAM XX SL Eagle Transmission
JARRUT	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
JARRUKAHVAT	SRAM Motive ULT, custom color
RATASPAKKA	SRAM XS 1299 Eagle Transmission, 10x52
KETJUT	SRAM XX SL Eagle Transmission
KAMPISARJA	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	CADEX Max XC WheelSystem, 30mm inner width
NAVAT	[F] CADEX Max XC, CenterLock [R]CADEX Max XC, 132t ratchet driver, CenterLock
PINNAT	CADEX Max XC carbon
RENKAAT	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
LISÄTIEDOT	tubeless prepared, MRP 1x CS chain guide
RAJOITTEET	
MAX RENGASVARA	2.4"
MAX KETJUN KOKO	34T

Suositusinta: 14 879,00 €

GEOMETRIA

RUNKO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	400	420	420	465	465	495		
Satulaputken kulma	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°			
Vaakaputken pituus (mm)	576 574	602 600	624 623	651 650				
Emäputken pituus (mm)	90	95	105	115				
Emäputken kulma	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°			
Haarukan offset (mm)	44	44	44	44				
Trail-mitta (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2				
Akseliväli (mm)	1141 1140	1168 1167	1192 1191	1221 1220				
Takahaarukan alaputken pituus (mm)	437 435	437 435	437 435	437 435				
Keskiön pudotus (mm)	51 45	51 45	52 45	52 45				
Stack-mitta (mm)	602 599	607 603	616 612	626 622				
Reach-mitta (mm)	420 425	445 450	465 470	490 495				
Standover-mitta (mm)	769 775	764 771	758 763	751 758				
Ohjaustangon leveys (mm)	780	780	780	780				
Ohjainkannattimen pituus (mm)	60	70	70	80				
Kammen pituus (mm)	170	170	175	175				

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.