

ANTHEM ADVANCED SL SE



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Stormfire Sprint
CADRE	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FOURCHE	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTISSEUR	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPOSANTS	
CINTRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
POIGNÉES	Giant XC Pro, silicone
POTENCE	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
TIGE DE SELLE	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SELLE	Giant Grit SLR
DÉRAILLEUR	
MANETTES	SRAM AXS Pod, 1x12
DÉRAILLEUR ARRIÈRE	SRAM XX SL Eagle Transmission
FREINS	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
LEVIER DE FREIN	SRAM Motive ULT, custom color
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAÎNE	SRAM XX SL Eagle Transmission
PÉDALIER	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	CADEX Max XC WheelSystem, 30mm inner width
MOYEUX	[F] CADEX Max XC, CenterLock [R] CADEX Max XC, 132t ratchet driver, CenterLock
RAYONS	CADEX Max XC carbon
PNEUS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITES	
DÉGAGEMENT MAX DES PNEUS	2.4"
TAILLE MAXIMALE DU PLATEAU	34T

Prix Public Conseillé: 14 000,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400		420		465		495	
Angle de tube de selle	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Longueur du tube supérieur (mm)	576	574	602	600	624	623	651	650
Longueur du tube de direction (mm)	90		95		105		115	
Angle du tube de direction	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Déport de fourche (mm)	44		44		44		44	
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Empattement (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Longueur des bases (mm)	437	435	437	435	437	435	437	435
Drop du boîtier de pédalier (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Hauteur en statique (mm)	769	775	764	771	758	763	751	758
Largeur de cintre (mm)	780		780		780		780	
Longueur de potence (mm)	60		70		70		80	
Longueur des manivelles (mm)	170		170		175		175	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.