



SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	White/Carbon
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTIZER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTE	
VOLAN	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
LULA VOLANA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
CIJEV SJEDALA	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SJEDALO	Giant Grit SLR
PEDALE	N/A
POGON	
RUČICE MJENJAČA	SRAM AXS Pod, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM XX SL Eagle Transmission
KOČNICE	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
RUČICE KOČNICA	SRAM Motive ULT
KAZETA	SRAM XS 1299 Eagle Transmission, 10x52
LANAC	SRAM XX SL Eagle Transmission
POGON	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant XCR WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
ŽBICE	Carbon
GUME	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODACI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dužina cijevi sjedala (mm)	400	420	465	485	520	540
Kut cijevi sjedala	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Dužina gornje cijevi (mm)	576	574	602	600	624	623
Dužina prednje cijevi (mm)	90	95	105	110	120	125
Kut vilice	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zakrivljenost vilice (offset) (mm)	44	44	44	44	44	44
Staza (mm)	116	112,2	115,9	112,2	115,9	112,2
Međuosovinski razmak kotača (mm)	1141	1140	1168	1167	1192	1191
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	437	435	437	435	437	435
Položaj osovine pogona (mm)	51	45	51	45	52	45
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	602	599	607	603	616	612
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	420	425	445	450	465	470
Prekoračna visina (mm)	769	775	764	771	758	763
Širina volana (mm)	780	780	780	780	780	780
Dužina lule volana (mm)	60	70	70	70	80	80
Dužina poluge pedale (mm)	170	170	170	175	175	175

Sve navedene specifikacije podložne su promjeni bez prethodne najave.