

ANTHEM ADVANCED SL SE



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Stormfire Sprint
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VOORVORK	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
DEMPER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	Giant XC Pro, silicone
STUURPEN	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ZADELPEN	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
ZADEL	Giant Grit SLR
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, 1x12
ACHTERDERAILLEUR	SRAM XX SL Eagle Transmission
REMMEN	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
REMHENDELS	SRAM Motive ULT, custom color
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
AANDRIJVING	SRAM XX SL Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	CADEX Max XC WheelSystem, 30mm inner width
NAVEN	[F] CADEX Max XC, CenterLock [R]CADEX Max XC, 132t ratchet driver, CenterLock
SPAKEN	CADEX Max XC carbon
BANDEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRA'S	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAXIMALE BANDENVRIJHEID	2.4"
MAXIMALE KETTINGBLADMAAT	34T

Adviesprijs: € 13.999,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400		420		465		495	
Zitbuis Hoek	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Frame Lengte (horizontaal) (mm)	576 574		602 600		624 623		651 650	
Balhoofdbuis Lengte (mm)	90		95		105		115	
Balhoofdbuis Hoek	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	116 112,2		115,9 112,2		115,9 112,2		115,8 112,2	
Wielbasis (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Liggende achtervork lengte (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Stand Over Height (mm)	769 775		764 771		758 763		751 758	
Stuur breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	60		70		70		80	
Cranklengte (mm)	170		170		175		175	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.