



## SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	White/Carbon
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
DEMPER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
STYRSTEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SETEPINNE	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SADEL	Giant Grit SLR
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM AXS Pod, 1x12
FRONTGIR	N/A
BAKGIR	SRAM XX SL Eagle Transmission
BREMSER	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BREMSEHENDLER	SRAM Motive ULT
KASSETT	SRAM XS 1299 Eagle Transmission, 10x52
KJEDE	SRAM XX SL Eagle Transmission
KRANK	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EIKE	Carbon
DEKK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°				
Top Tube Length (mm)	576   574	602   600	624   623	651   650				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	116   112,2	115,9   112,2	115,9   112,2	115,8   112,2				
Wheelbase (mm)	1141   1140	1168   1167	1192   1191	1221   1220				
Chain Stay Length (mm)	437   435	437   435	437   435	437   435				
Bottom Bracket Drop (mm)	51   45	51   45	52   45	52   45				
Stack (mm)	602   599	607   603	616   612	626   622				
Reach (mm)	420   425	445   450	465   470	490   495				
Stand Over Height (mm)	769   775	764   771	758   763	751   758				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	60	70	70	80				
Crank Length (mm)	170	170	175	175				

Alle spesifikasjonene kan endres uten varsel.