

ANTHEM ADVANCED SL SE



SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	White/Carbon
QUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORQUILHA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTECEDORES	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTES	
GUIADOR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PUNHOS	Giant XC Pro, silicone
AVANÇO	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
ESPIGÃO DE SELIM	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SELIM	Giant Grit SLR
PEDAIS	N/A
TRANSMISSÃO	
MANETES	SRAM AXS Pod, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM XX SL Eagle Transmission
TRAVÕES	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	SRAM Motive ULT
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CORRENTE	SRAM XX SL Eagle Transmission
CONJUNTO PEDALEIRO	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant XCR WheelSystem
CUBOS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAIOS	Carbon
PNEUS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Preço: 10 949,00 €

GEOMETRIA

QUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Comprimento do tubo do assento (mm)	400		420		465		495	
Ângulo do tubo do assento	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Comprimento do tubo superior (mm)	576	574	602	600	624	623	651	650
Comprimento do tubo principal (mm)	90		95		105		115	
Ângulo do tubo principal	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Garfo ancinho (mm)	44		44		44		44	
Trilha (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
distância entre eixos (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Comprimento Chain Stay (mm)	437	435	437	435	437	435	437	435
Suporte inferior (mm)	51	45	51	45	52	45	52	45
Pilha (mm)	602	599	607	603	616	612	626	622
Alcançar (mm)	420	425	445	450	465	470	490	495
Altura do standover (mm)	769	775	764	771	758	763	751	758
Largura do guidão (mm)	780		780		780		780	
Comprimento da haste (mm)	60		70		70		80	
Comprimento da Manivela (mm)	170		170		175		175	

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.