



SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	White/Carbon
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FURCA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SOC	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTE	
GHIDON	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
PIPA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
TIJA SA	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SA	Giant Grit SLR
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM AXS Pod, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM XX SL Eagle Transmission
FRANE	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
MANETE FRANA	SRAM Motive ULT
PINIOANE	SRAM XS 1299 Eagle Transmission, 10x52
LANT	SRAM XX SL Eagle Transmission
ANGRENAJ	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant XCR WheelSystem
BUTUCI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPITE	Carbon
ANVELOPE	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIE

CADRU	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Top Tube Length (mm)	576 574	602 600	624 623	651 650
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Wheelbase (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stand Over Height (mm)	769 775	764 771	758 763	751 758
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	70	70	80
Crank Length (mm)	170	170	175	175

Toate specificatiile enumerate se pot schimba fara notificare prealabila.