

ANTHEM ADVANCED SL SE



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	White/Carbon
RÁM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VIDLICA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
TLMIČ	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTY	
RIADIDLÁ	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPY	Giant XC Pro, silicone
PREDSTAVEC	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SEDOVKA	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SEDADLO	Giant Grit SLR
PEDÁLE	N/A
POHON	
RADENIE	SRAM AXS Pod, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM XX SL Eagle Transmission
BRZDY	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	SRAM Motive ULT
KAZETA	SRAM XS 1299 Eagle Transmission, 10x52
REŤAZ	SRAM XX SL Eagle Transmission
KLUKY	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant XCR WheelSystem
NÁBOJE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
ŠPICE	Carbon
PNEUMATIKY	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DOPLNKY	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Cena: 12 999 €

GEOMETRIA

RÁM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dĺžka sedlovej trubky (mm)	400		420		465		495	
Uhol sedlovej trubky	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Dĺžka hornej rámovej trubky (mm)	576	574	602	600	624	623	651	650
Dĺžka hlavovej trubky (mm)	90		95		105		115	
Uhol hlavovej trubky	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Offset vidlice (mm)	44		44		44		44	
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Rázvor (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Dĺžka zadnej stavby (mm)	437	435	437	435	437	435	437	435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	51	45	51	45	52	45	52	45
Stack - výška riadenia (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Výška rámu od zeme (mm)	769	775	764	771	758	763	751	758
Šírka riaditok (mm)	780		780		780		780	
Dĺžka predstavca (mm)	60		70		70		80	
Dĺžka klúku (mm)	170		170		175		175	

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.