



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	White/Carbon
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTIZER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTE	
KRMILO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant XC Pro, silicone
OPORA KRMILA	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
OPORA SEDEŽA	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SEDEŽ	Giant Grit SLR
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM XX SL Eagle Transmission
ZAVORE	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	SRAM Motive ULT
VERIŽNIK	SRAM XS 1299 Eagle Transmission, 10x52
VERIGA	SRAM XX SL Eagle Transmission
GONILKE Z VERIŽNIKI	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCR WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
NAPERE	Carbon
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		420		465		495	
Kot sedežne cevi	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Višina glave okvirja (mm)	90		95		105		115	
Krmilni kot	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	116	112,2	115,9	112,2	115,9	112,2	115,8	112,2
Medosna razdalja (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Dolžina cevi ob verigi (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Oddaljenost zgornje cevi od gonilne osi (mm)	602	599	607	603	616	612	626	622
Doseg (mm)	420	425	445	450	465	470	490	495
Višina zgornje cevi (mm)	769	775	764	771	758	763	751	758
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	60		70		70		80	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.